

\$GLOBALS['TCA'] (Array für Tabellenkonfiguration)

Konfiguration

\$GLOBALS['TCA'] (Array für Tabellenkonfiguration)

Suchbegriff eingeben:

feuser|fe_user

Regulären Ausdruck verwenden

Suchen

```
backend_layout
be_groups
be_users
fe_groups
fe_users
  columns
    address
    city
    company
    country
    crdate
    config
    exclude = 1
    label =LLL:EXT:femanager/Resources/Private/Language/locallang_db.xlf:fe_users.crdate
  date_of_birth
  disable
  email
  endtime
  fax
  felogin_forgotHash
  felogin_redirectPid
  first_name
  gender
  image
  lastlogin
  last_name
  lockToDomain
    config
    exclude = 1
    label =LLL:EXT:frontend/Resources/Private/Language/locallang_tca.xlf:fe_users.lockToDomain
  middle_name
  module_sys_dmail_category
    config
      foreign_table = sys_dmail_category
      foreign_table_where = AND sys_dmail_category.l18n_parent=0 AND sys_dmail_category.pid IN (###PAGE_TSCONFIG_IDLIST###) ORDER BY sys_dmail_cat
      itemsProcFunc = DirectMailTeam\DirectMail\SelectCategories->get_localized_categories
      itemsProcFunc_config
      maxitems = 60
      minitems = 0
      MM = sys_dmail_feuser_category_mm
      renderMode = checkbox
      renderType = selectCheckBox
      size = 5
      type = select
    exclude = 1
    label =LLL:EXT:direct_mail/Resources/Private/Language/locallang_tca.xlf:module_sys_dmail_group.category
  module_sys_dmail_html
  module_sys_dmail_newsletter
  name
  password
    config
      label =LLL:EXT:frontend/Resources/Private/Language/locallang_tca.xlf:fe_users.password
  starttime
  telephone
  title
  TSconfig
  timestamp
    config
    exclude = 1
```

\$GLOBALS['TCA'] (Array für Tabellenkonfiguration)

```
default = 0
items
0
0 = LLL:EXT:extbase/Resources/Private/Language/locallang_db.xlf:fe_users.tx_extbase_type.0
1 = 0
1
0 = LLL:EXT:extbase/Resources/Private/Language/locallang_db.xlf:fe_users.tx_extbase_type.Tx_Extbase_Domain_Model_FrontendUser
1 = Tx_Extbase_Domain_Model_FrontendUser
maxitems = 1
renderType = selectSingle
size = 1
type = select
exclude = 1
label = LLL:EXT:extbase/Resources/Private/Language/locallang_db.xlf:fe_users.tx_extbase_type
tx_femanager_changerequest
config
exclude = 1
label = LLL:EXT:femanager/Resources/Private/Language/locallang_db.xlf:fe_users.changerequest
tx_femanager_confirmedbyadmin
config
exclude = 1
label = LLL:EXT:femanager/Resources/Private/Language/locallang_db.xlf:fe_users.registrationconfirmedbyadmin
tx_femanager_confirmedbyuser
config
exclude = 1
label = LLL:EXT:femanager/Resources/Private/Language/locallang_db.xlf:fe_users.registrationconfirmedbyuser
tx_femanager_log
config
exclude = 1
label = LLL:EXT:femanager/Resources/Private/Language/locallang_db.xlf:fe_users.log
tx_savlibraryexample8_address
config
exclude = 1
label = LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_address
tx_savlibraryexample8_city
config
exclude = 1
label = LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_city
tx_savlibraryexample8_company
config
exclude = 1
label = LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_company
tx_savlibraryexample8_country
config
exclude = 1
label = LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_country
tx_savlibraryexample8_email
config
exclude = 1
label = LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_email
tx_savlibraryexample8_fax
config
exclude = 1
label = LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_fax
tx_savlibraryexample8_image
config
exclude = 1
label = LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_image
tx_savlibraryexample8_name
config
exclude = 1
label = LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_name
tx_savlibraryexample8_password
config
exclude = 1
label = LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_password
tx_savlibraryexample8_special
config
exclude = 1
label = LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_special
tx_savlibraryexample8_telephone
```

```
$GLOBALS['TCA'] (Array für Tabellenkonfiguration)
```

```
tx_savlibraryexample8_title
    config
        exclude = 1
        label =LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_title
tx_savlibraryexample8_TSconfig
    config
        exclude = 1
        label =LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_TSconfig
tx_savlibraryexample8_usergroup
    config
        exclude = 1
        label =LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_usergroup
tx_savlibraryexample8_www
    config
        exclude = 1
        label =LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_www
tx_savlibraryexample8_zip
    config
        exclude = 1
        label =LLL:EXT:sav_library_example8/Resources/Private/Language/locallang_db.xml:fe_users.tx_savlibraryexample8_zip
usergroup
    config
        label =LLL:EXT:frontend/Resources/Private/Language/locallang_tca.xlf:fe_users.usergroup
username
    config
        label =LLL:EXT:frontend/Resources/Private/Language/locallang_tca.xlf:fe_users.username
www
zip
ctrl
    crdate = crdate
    cruser_id = cruser_id
    default_sortby = ORDER BY username
    delete = deleted
    enablecolumns
    fe_cruser_id = fe_cruser_id
    label = username
    searchFields = username,name,first_name,last_name,middle_name,address,telephone,fax,email,title,zip,city,country,company
    title =LLL:EXT:frontend/Resources/Private/Language/locallang_tca.xlf:fe_users
    tstamp = tstamp
    type = tx_extbase_type
    typeicon_classes
    useColumnsForDefaultValues = usergroup,lockToDomain,disable,starttime,endtime
feInterface
interface
palettes
types
0
    showitem = disable,username,password,usergroup,lastlogin,--div--;LLL:EXT:frontend/Resources/Private/Language/locallang_tca.xlf:fe_users.tabs.per
Tx_Extbase_Domain_Model_FrontendUser
    showitem = disable,username,password,usergroup,lastlogin,--div--;LLL:EXT:frontend/Resources/Private/Language/locallang_tca.xlf:fe_users.tabs.per
pages
columns
abstract
alias
author
author_email
backend_layout
backend_layout_next_level
cache_tags
cache_timeout
categories
content_from_pid
description
doktype
editlock
endtime
extendToSubpages
fe_group
fe_login_mode
hidden
is_siteroot
```

```
$GLOBALS['TCA'] (Array für Tabellenkonfiguration)
```

```
layout
media
module
config
    default =
    items
        0
        1
            0 = LLL:EXT:frontend/Resources/Private/Language/locallang_tca.xlf:pages.module.I.4
            1 = fe_users
            2 = status-user-frontend
        2
        3
        4
        5
    renderType = selectSingle
    type = select
exclude = 1
label = LLL:EXT:frontend/Resources/Private/Language/locallang_tca.xlf:pages.module
mount_pid
mount_pid_ol
nav_hide
nav_title
newUntil
no_cache
no_search
php_tree_stop
shortcut
shortcut_mode
starttime
subtitle
t3ver_label
target
title
TSconfig
tsconfig_includes
tx_ddgooglesitemap_change_frequency
tx_ddgooglesitemap_lastmod
tx_ddgooglesitemap_priority
tx_impexp_origuid
url
urlype
url_scheme
ctrl
    crdate = crdate
    cruser_id = cruser_id
    delete = deleted
    editlock = editlock
    enablecolumns
    hideAtCopy = 1
    label = title
    origUid = t3_origuid
    prependAtCopy = LLL:EXT:lang/locallang_general.xlf:LGL.prependAtCopy
    searchFields = title,alias,nav_title,subtitle,url,keywords,description,abstract,author,author_email
    sortby = sorting
    title = LLL:EXT:lang/locallang_tca.xlf:pages
    transForeignTable = pages_language_overlay
    tstamp = tstamp
    type = doktype
    typeicon_classes
        1 = apps-pagetree-page-default
        1-hideinmenu = apps-pagetree-page-not-in-menu
        1-root = apps-pagetree-page-domain
        3 = apps-pagetree-page-shortcut-external
        3-hideinmenu = apps-pagetree-page-shortcut-external-hideinmenu
        3-root = apps-pagetree-page-shortcut-external-root
        4 = apps-pagetree-page-shortcut
        4-hideinmenu = apps-pagetree-page-shortcut-hideinmenu
        4-root = apps-pagetree-page-shortcut-root
        6 = apps-pagetree-page-backend-users
        6-hideinmenu = apps-pagetree-page-backend-users-hideinmenu
```

```
$GLOBALS['TCA'] (Array für Tabellenkonfiguration)
```

```
    7-root = apps-pagetree-page-mountpoint-root
    199 = apps-pagetree-spacer
    199-hideinmenu = apps-pagetree-spacer
    199-root = apps-pagetree-page-domain
    254 = apps-pagetree-folder-default
    254-hideinmenu = apps-pagetree-folder-default
    254-root = apps-pagetree-page-domain
    255 = apps-pagetree-page-recycler
    255-hideinmenu = apps-pagetree-page-recycler
    contains-approve = apps-pagetree-folder-contains-approve
    contains-board = apps-pagetree-folder-contains-board
    contains-dmail = tcarecords-pages-contains-dmail
    contains-events = tcarecords-pages-contains-events
    contains-fe_users = apps-pagetree-folder-contains-fe_users
    contains-news = apps-pagetree-folder-contains-news
    contains-shop = apps-pagetree-folder-contains-shop
    contains-t3blog = tcarecords-pages-contains-t3blog
    default = apps-pagetree-page-default
    page-contentFromPid = apps-pagetree-page-content-from-page
    page-contentFromPid-hideinmenu = apps-pagetree-page-content-from-page-hideinmenu
    page-contentFromPid-root = apps-pagetree-page-content-from-page-root
    typeicon_column = doktype
    useColumnsForDefaultValues = doktype,fe_group,hidden
    versioningWS = 1
    interface
    palettes
    types
    pages_language_overlay
    sys_category
    sys_collection
    sys_dmail
    sys_dmail_category
    sys_dmail_group
        columns
            csv
            description
            list
            mail_groups
            pages
            query
            recursive
            select_categories
            static_list
                config
                    allowed = tt_address,fe_users,fe_groups
                    internal_type = db
                    maxitems = 100000
                    minitems = 0
                    MM = sys_dmail_group_mm
                    show_thumbs = 1
                    size = 20
                    type = group
                    wizards
                label =LLL:EXT:direct_mail/Resources/Private/Language/locallang_tca.xlf:sys_dmail_group.static_list
                title
                type
                whichtables
            ctrl
            interface
            types
    sys_domain
    sys_file
    sys_filemounts
    sys_file_collection
    sys_file_metadata
    sys_file_reference
    sys_file_storage
    sys_history
    sys_language
    sys_log
    sys_news
```

```
$GLOBALS['TCA'] (Array für Tabellenkonfiguration)
```

```
tt_content
tx_amtfeedimporter_domain_model_feed
tx_bootstrappackage_accordion_item
tx_bootstrappackage_carousel_item
tx_bootstrappackage_tab_item
tx_devlog_domain_model_entry
tx_extensionmanager_domain_model_extension
tx_extensionmanager_domain_model_repository
tx_femanager_domain_model_log
tx_gridelements_backend_layout
tx_newsletter_domain_model_bounceaccount
tx_newsletter_domain_model_email
tx_newsletter_domain_model_link
tx_newsletter_domain_model_newsletter
tx_newsletter_domain_model_recipientlist
tx_news_domain_model_link
tx_news_domain_model_news
tx_news_domain_model_tag
tx_powermail_domain_model_answer
tx_powermail_domain_model_field
    columns
        auto_marker
        content_element
        create_from_typoscript
        css
        datepicker_settings
        description
        endtime
        feuser_value
            config
                eval =
            items
                0
                1
                    0 = LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_field.feuser_value.name
                    1 = name
                2
                    0 = LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_field.feuser_value.address
                    1 = address
                3
                    0 = LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_field.feuser_value.phone
                    1 = telephone
                4
                    0 = LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_field.feuser_value.fax
                    1 = fax
                5
                    0 = LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_field.feuser_value.email
                    1 = email
                6
                    0 = LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_field.feuser_value.zip
                    1 = zip
                7
                    0 = LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_field.feuser_value.city
                    1 = city
                8
                    0 = LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_field.feuser_value.country
                    1 = country
                9
                    0 = LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_field.feuser_value.www
                    1 = www
                10
                    0 = LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_field.feuser_value.company
                    1 = company
            itemsProcFunc = In2code\Powermail\Tca\AddOptionsToSelection->addOptionsForFeUserProperty
            maxitems = 1
            renderType = selectSingle
            size = 1
            type = select
            exclude = 1
            l10n_mode = exclude
        label = LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_field.feuser_value
```

```
$GLOBALS['TCA'] (Array für Tabellenkonfiguration)
```

```
mandatory
marker
multiselect
own_marker_select
pages
path
placeholder
prefill_value
sender_email
sender_name
settings
sorting
starttime
sys_language_uid
t3ver_label
text
title
type
validation
validation_configuration
ctrl
interface
    showRecordFieldList = sys_language_uid, l10n_parent, l10n_diffsource, hidden, title, type, settings, path, content_element, text, prefill_value, pl:
palettes
    1
    2
    3
        canNotCollapse = 1
        showitem = prefill_value, placeholder, feuser_value, create_from_typoscript
    4
    5
    21
    31
        canNotCollapse = 1
        showitem = prefill_value, feuser_value
    32
        canNotCollapse = 1
        showitem = prefill_value, placeholder, feuser_value
    33
        canNotCollapse = 1
        showitem = feuser_value, create_from_typoscript
    41
    42
    43
        canNotCollapse = 1
types
tx_powermail_domain_model_form
tx_powermail_domain_model_mail
    columns
        answers
        body
        crdate
        endtime
        feuser
            config
                allowed = fe_users
                default = 0
                internal_type = db
                maxitems = 1
                minitems = 0
                size = 1
                type = group
            exclude = 1
            label =LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_mail.feuser
form
hidden
l10n_diffsource
l10n_parent
marketing_browser_language
marketing_country
marketing_frontend_language
```

```
$GLOBALS['TCA'] (Array für Tabellenkonfiguration)
```

```
marketing_referer_domain
receiver_mail
sender_ip
sender_mail
sender_name
spam_factor
starttime
subject
sys_language_uid
t3ver_label
time
uid
user_agent
ctrl
interface
    showRecordFieldList = sys_language_uid, l10n_parent, l10n_diffsource, hidden, crdate, receiver_mail, sender_name, sender_mail, subject, form, answer
palettes
types
1
    columnsOverrides
        showitem = crdate,receiver_mail,--palette--;LLL:EXT:powermail/Resources/Private/Language/locallang_db.xlf:tx_powermail_domain_model_mail.palette
tx_powermail_domain_model_page
tx_rtehtmlarea_acronym
tx_savlibraryplus_export_configuration
tx_scheduler_task_group
tx_sfeventmgt_domain_model_customnotificationlog
tx_sfeventmgt_domain_model_event
tx_sfeventmgt_domain_model_location
tx_sfeventmgt_domain_model_organisator
tx_sfeventmgt_domain_model_priceoption
tx_sfeventmgt_domain_model_registration
    columns
        acceptttc
        address
        amount_of_registrations
        city
        company
        confirmation_until
        confirmed
        country
        date_of_birth
        email
        endtime
        event
        fe_user
            config
                allowed = fe_users
                foreign_table = fe_users
                internal_type = db
                maxitems = 1
                minitems = 0
                size = 1
                type = group
                wizards
            exclude = 1
            label = LLL:EXT:sf_event_mgt/Resources/Private/Language/locallang_db.xlf:tx_sfeventmgt_domain_model_registration.fe_user
firstname
gender
hidden
ignore_notifications
l10n_diffsource
l10n_parent
language
lastname
main_registration
notes
paid
paymentmethod
payment_reference
phone
recaptcha
```

```
$GLOBALS['TCA'] (Array für Tabellenkonfiguration)
```

```
title
waitlist
zip
ctrl
    crdate = crdate
    cruser_id = cruser_id
    delete = deleted
    dividers2tabs = 1
    enablecolumns
    iconfile = EXT:sf_event_mgt/Resources/Public/Icons/tx_sfeventmgt_domain_model_registration_unconfirmed.gif
    label = firstname
    label_alt = lastname, email
    label_alt_force = 1
    languageField = sys_language_uid
    searchFields = firstname,lastname,address,zip,city,phone,email,gender,confirmed,paid,paymentmethod,payment_reference,notes,fe_user,waitlist,
    sortby = sorting
    title = LLL:EXT:sf_event_mgt/Resources/Private/Language/locallang_db.xlf:tx_sfeventmgt_domain_model_registration
    transOrigDiffSourceField = l10n_diffsource
    transOrigPointerField = l10n_parent
    tstamp = tstamp
    typeicons
    typeicon_column = confirmed
    versioningWS = 2
    versioning_followPages = 1
interface
    showRecordFieldList = sys_language_uid, l10n_parent, l10n_diffsource, hidden, firstname, lastname, title, company, address, zip, city, country, phone,
palettes
types
    1
        showitem = sys_language_uid,l10n_parent,l10n_diffsource,hidden,--palette--;1,firstname,lastname,title,company,address,zip,city,country,phone,en
tx_t3blog_blog_nl
tx_t3blog_cat
tx_t3blog_com
tx_t3blog_com_nl
tx_t3blog_pingback
tx_t3blog_post
tx_t3blog_trackback
tx_t3socials_networks
```