

TYPO3 Core - Bug #20060

IPmaskList - shows just white page instead of BE-Login

2009-02-20 11:25 - Daniel Brüßler

Status: Closed	Start date: 2009-02-20
Priority: Should have	Due date:
Assignee:	% Done: 0%
Category:	Estimated time: 0.00 hour
Target version:	Complexity:
TYPO3 Version: 4.2	Is Regression:
PHP Version: 5.2	Sprint Focus:
Tags:	

Description

when a developer puts an IP in
\$TYPO3_CONF_VARS['BE']['IPmaskList']

all other IPs just get a white page

=> correct behaviour would be to block debug() messages for other IPs in BE

edit localconf.php

put a not existing IP in

```
$TYPO3_CONF_VARS['BE']['IPmaskList'] = '1.2.3.4.1';
```

visit "http://www.DOMAIN.XYZ/typo3/"

(issue imported from #M10502)

History

#1 - 2009-02-20 11:30 - Daniel Brüßler

PHP versions tested: 5.1.x, 5.2.8

#2 - 2009-02-24 08:39 - Ernesto Baschny

This is the documented behaviour of that setting:

[BE][IPmaskList] = String. Lets you define a list of IP-numbers (with *-wildcards) that are the ONLY ones allowed access to ANY backend activity. On error an error header is sent and the script exits. Works like IP masking for users configurable through TSconfig.

You are probably mixing it up with [SYS][devIPmask], which is described as:

Defines a list of IP addresses which will allow development-output to display. The debug() function will use this as a filter.