

## TYPO3 Core - Bug #21078

### Optimize disposal of t3lib\_PageRenderer

2009-09-17 17:08 - Oliver Hader

<b>Status:</b>	Closed	<b>Start date:</b>	2009-09-17
<b>Priority:</b>	Must have	<b>Due date:</b>	
<b>Assignee:</b>	Oliver Hader	<b>% Done:</b>	0%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>		<b>Complexity:</b>	
<b>TYPO3 Version:</b>	4.3	<b>Is Regression:</b>	
<b>PHP Version:</b>	5.2	<b>Sprint Focus:</b>	
<b>Tags:</b>			

#### Description

t3lib\_PageRenderer is currently used in the TYPO3 backend and frontend. There the classes template and tslib\_fe inherit from t3lib\_PageRenderer. However, in frontend disposal it's not required to have the feature set of the page renderer loaded if a request gets served by the cache and nothing is rendered at all.

Thus, instead of using "tslib\_fe extends t3lib\_PageRenderer", an aggregation shall be used.  
Extension can then access the page renderer e.g. by \$TSFE->getPageRenderer()->addJsFile()

(issue imported from #M11985)

#### History

##### #1 - 2009-09-17 20:00 - Oliver Hader

Committed to SVN Trunk (rev. 5955)

#### Files

0011985.patch	39.9 KB	2009-09-17	Administrator Admin
---------------	---------	------------	---------------------