

## TYPO3 Core - Bug #28685

### t3lib\_div::getIndpEnv('REQUEST\_URI') does not return fragment/hash of url

2011-08-02 16:50 - Simon Schaufelberger

<b>Status:</b>	Closed	<b>Start date:</b>	2011-08-02
<b>Priority:</b>	Should have	<b>Due date:</b>	
<b>Assignee:</b>		<b>% Done:</b>	0%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>		<b>Complexity:</b>	
<b>TYPO3 Version:</b>	4.5	<b>Is Regression:</b>	
<b>PHP Version:</b>		<b>Sprint Focus:</b>	
<b>Tags:</b>			

#### Description

As written in the comment in the function getIndpEnv, this function does not handle the fragment (the text after # in the url) which is not good if you really need that part of a url. Of course there are workarounds but still, this IS a bug and should be fixed. I for example need this to trigger a jQuery function and for that i need that hash after a redirect with the loginbox

#### History

##### #1 - 2011-08-02 17:02 - Simon Schaufelberger

this is the way how it will work:

<http://stackoverflow.com/questions/940905/can-php-read-the-hash-portion-of-the-url#answer-940996>

<http://www.php.net/manual/en/function.parse-url.php>

```
parse_url("http://foo?bar#fizzbuzz", PHP_URL_FRAGMENT);
```

output:

```
fizzbuzz
```

##### #2 - 2011-08-02 17:13 - Simon Schaufelberger

The Fragment is never sent to the server. So, this might be impossible unless you use AJAX to change the page after the fact.

Another idea would be to have Javascript turn the hash into a \$\_GET paramater, and then refresh the page.

ok, so this will not work. :(

It is acuatally not a php but a browser bug, see: <https://bugs.php.net/bug.php?id=25804>

##### #3 - 2011-08-03 13:06 - Oliver Hader

- Status changed from New to Closed

So no change required here.