

TYPO3 Core - Bug #48300

Entrylevel wrong when switching languages

2013-05-16 17:54 - Florian Scholz

Status:	Closed	Start date:	2013-05-16
Priority:	Should have	Due date:	
Assignee:		% Done:	100%
Category:	TypoScript	Estimated time:	0.00 hour
Target version:		Complexity:	
TYPO3 Version:	6.1	Is Regression:	
PHP Version:		Sprint Focus:	
Tags:			

Description

In a multi-language setup, I get different entrylevel outputs when switching from the default language (German) to another language (English)

Defined value is entrylevel = 1, however the English version behaves like there would have been set entrylevel = 0 in the TypoScript.

Any ideas?

Language settings:

```
config {
    linkVars = L
    htmlTag_langKey = de_DE
    sys_language_uid = 0
    language = de
    locale_all = de_DE
    sys_language_overlay = 1
}

// Language Englisch
[globalVar = GP:L = 1]
    config.linkVars = L
    config.sys_language_uid = 1
    config.language = en
    config.locale_all = en_GB
    config.htmlTag_langKey = en_GB
[global]
```

Menu TypoScript:

```
SUBNAVI = COA_INT
SUBNAVI = HMENU
SUBNAVI {
    entryLevel = 1

    1 = TMENU

    1 {

        wrap = <ul class="subMnu">|</ul>
        noBlur = 0
        NO = 1
        NO.wrapItemAndSub = <li class="subMnuSingleBlue">|</li>
        CUR < .NO
        CUR.ATagParams = class="act "

        IFSUB = 1
        IFSUB.wrapItemAndSub = <li class="subMnuBlue">|</li>
```

```

CURIFSUB < .IFSUB
CURIFSUB.ATagParams = class="act "

ACT = 1
ACT < .NO
ACTIFSUB < .CURIFSUB
}

2 = TMENU
2 {

wrap = <ul class="subMnu">|</ul>
NO = 1
NO.wrapItemAndSub = <li class = "subMnuGrey">|</li>
CUR < .NO
CUR.ATagParams = class="act "
ACT = 1
ACT < .CUR

}
}

```

(c.f. <http://www.typo3.net/forum/beitraege/mehrsprachigkeit/114479/>)

Associated revisions

Revision 925ce3fa - 2013-06-15 14:38 - Alexander Stehlik

[BUGFIX] Fix template rootline for translated pages

The TypoScript template rootline in the Frontend will not be changed any more if a different sys_language_uid is used.

The data of the current rootLine will be overwritten with the translated rootLine data.

Resolves: #48300

Releases: 6.2, 6.1

Change-Id: I38bd4a6f3d3c2f15712003b1d1a1334284ebe9b0

Reviewed-on: <https://review.typo3.org/21174>

Reviewed-by: Wouter Wolters

Tested-by: Wouter Wolters

Revision d5b2763d - 2013-06-15 14:41 - Alexander Stehlik

[BUGFIX] Fix template rootline for translated pages

The TypoScript template rootline in the Frontend will not be changed any more if a different sys_language_uid is used.

The data of the current rootLine will be overwritten with the translated rootLine data.

Resolves: #48300

Releases: 6.2, 6.1

Change-Id: I38bd4a6f3d3c2f15712003b1d1a1334284ebe9b0

Reviewed-on: <https://review.typo3.org/21449>

Reviewed-by: Wouter Wolters

Tested-by: Wouter Wolters

History

#1 - 2013-05-16 18:19 - Philipp Gampe

- Status changed from New to Needs Feedback

Are you sure that you created translations for all pages?

#2 - 2013-05-16 18:30 - Philipp Gampe

I can not reproduce this. Please share more details, best would be an export of a sample page tree including the TS.

#3 - 2013-05-29 04:45 - Jochen Weber

same issue.

when i increment the entryLevel within a condition to the language(!=0), everything works like expected.
i also disabled the realurl-extension to exclude this. i will create an sample export next days...

#4 - 2013-05-29 12:25 - Jochen Weber

the range of "special = rootline" also starts at the wrong point.
i defined a page with "is_siteroot", but in a other language as default, it is ignored.

#5 - 2013-05-31 13:05 - Alexander Stehlik

I think i found the Problem in

```
\TYPO3\CMS\Frontend\Controller\TypoScriptFrontendController::updateRootLinesWithTranslations()
```

In this method the rootline of the template is overwritten which look pretty dirty to me:

```
$this->tmpl->rootLine = array_reverse($this->sys_page->getRootLine($this->id, $this->MP));
```

The rootline of the template should be initialized by passing it to the start() method of the TemplateService
(\TYPO3\CMS\Core\TypoScript\TemplateService::start(\$theRootLine)). Otherwise configuration options like "root" of the template are totally ignored.

The change was committed with [51f41665](#) and reviewed here: <https://review.typo3.org/#/c/16992/>

#6 - 2013-05-31 13:17 - Alexander Stehlik

- File test_bug_48300.t3d added

To test the problem you have two options:

1. use config.sys_language_mode = content_fallback; 0
2. add a language record to the sub root page

I attach a small page tree export where you can test the problem:

1. in the TYPO3 root create a "Alternative Page Language" record (e.g. English) **with UID 2**
2. import the t3d file
3. navigate to page subroot1 - page 1.1 (has a language record)
4. append &L=2 to URL

Expected behavior: The menu structure should not change

Current behavior: The menu is now linking to the root pages.

#7 - 2013-05-31 17:12 - Gerrit Code Review

- Status changed from Needs Feedback to Under Review

Patch set 1 for branch **master** has been pushed to the review server.
It is available at <https://review.typo3.org/21174>

#8 - 2013-06-04 11:52 - Florian Scholz

Can we please have this in a 6.1.x release? I consider this as a major bug.

#9 - 2013-06-05 10:12 - Gerrit Code Review

Patch set 2 for branch **master** has been pushed to the review server.
It is available at <https://review.typo3.org/21174>

#10 - 2013-06-15 14:37 - Gerrit Code Review

Patch set 3 for branch **master** has been pushed to the review server.
It is available at <https://review.typo3.org/21174>

#11 - 2013-06-15 14:40 - Gerrit Code Review

Patch set 1 for branch **TYPO3_6-1** has been pushed to the review server.
It is available at <https://review.typo3.org/21449>

#12 - 2013-06-15 15:30 - Alexander Stehlik

- Status changed from Under Review to Resolved

- % Done changed from 0 to 100

Applied in changeset [d5b2763d018f256f99120db69f9f0af2f65635e3](#).

#13 - 2018-10-02 12:14 - Benni Mack

- Status changed from Resolved to Closed

Files

test_bug_48300.t3d	3.84 KB	2013-05-31	Alexander Stehlik
--------------------	---------	------------	-------------------