

TYPO3.Surf - Bug #62319

Enhance Task SymlinkConfigurationTask to use not only the Production context

2014-10-18 14:41 - Johannes Steu

Status:	Resolved	Start date:	2014-10-18
Priority:	Should have	Due date:	
Assignee:		% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:			
Description			
For deployment i'd like to use the SymlinkConfigurationTask for all Contexts. If you deploy your Application on different Nodes and run an separate testing Builds the Configuration could be stored in shared/Configuration/Testing. Same for the Development Context for Develop-Builds. Therefore the SymlinkConfigurationTask could use \$application->getContext().			

History

#1 - 2014-10-18 14:44 - Johannes Steu

An implementation could look like this

```
$targetReleasePath = $deployment->getApplicationReleasePath($application);  
  
$context = $application->getContext();  
  
if($context === NULL || $context == "") {  
    throw new \TYPO3\Surf\Exception\InvalidConfigurationException("No context is configured");  
}  
  
$commands = array(  
    "cd {$targetReleasePath}/Configuration",  
    "rm -rf ".$context."/*",  
    "if [ -d ".$context." ]; then rmdir ".$context."; fi",  
    "mkdir -p ../../../../shared/Configuration/".$context.,  
    "ln -snf ../../../../shared/Configuration/".$context." ".$context.  
);  
$this>shell->executeOrSimulate($commands, $node, $deployment);
```

#2 - 2015-01-22 16:08 - Christopher Hlubek

- Status changed from New to Resolved

This is fixed with <https://review.typo3.org/#/c/33970/>