

## TYPO3 Core - Bug #77994

### cObject RECORDS - conf property problem with plugins

2016-09-19 13:58 - Stig Nørgaard Færch

|                        |                      |                        |            |
|------------------------|----------------------|------------------------|------------|
| <b>Status:</b>         | New                  | <b>Start date:</b>     | 2016-09-19 |
| <b>Priority:</b>       | Should have          | <b>Due date:</b>       |            |
| <b>Assignee:</b>       |                      | <b>% Done:</b>         | 0%         |
| <b>Category:</b>       | Fluid Styled Content | <b>Estimated time:</b> | 0.00 hour  |
| <b>Target version:</b> |                      | <b>Complexity:</b>     |            |
| <b>TYPO3 Version:</b>  | 7                    | <b>Is Regression:</b>  | No         |
| <b>PHP Version:</b>    |                      | <b>Sprint Focus:</b>   |            |
| <b>Tags:</b>           |                      |                        |            |

#### Description

This is probably also true for cObject CONTENT

If you want to modify rendering of a tt\_content based content rendered by RECORDS, it will not work if you base it upon the tt\_content cObject:

For example:

```
test = RECORDS
test.source = {someId}
test.tables = tt_content
test.conf.tt_content < tt_content
test.conf.tt_content.list.20.cal_controller.some_property = 123
```

I think the reason is the way the plugin it self is rendered with fluid\_styled\_content here:

/var/www/typo3sources/typo3\_src-7.6.7/typo3/sysex/typo3fluid\_styled\_content/Resources/Private/Templates/List.html

I found another way which works:

```
tt_content.list.20 = CASE
tt_content.list.20.key.field = list_type
tt_content.list.variables {
    plugin = < tt_content.list.20
}
```

and then add the {plugin} variable to the above mentioned template instead of using the f:cObject viewhelper:

```
<html xmlns:f="http://typo3.org/ns/TYPO3/CMS/Fluid/ViewHelpers" data-namespace-typo3-fluid="true">
<f:layout name="HeaderContentFooter" />

<f:section name="content">
    {plugin -> f:format.raw()}
</f:section>
</html>
```

#### History

#1 - 2016-09-19 18:54 - Wouter Wolters

- Assignee deleted (Benni Mack)