

TYPO3 Core - Task #84717

Reconsider serialized array for Linkvalidator

2018-04-13 21:25 - Sybille Peters

Status: Closed	Start date: 2019-12-13
Priority: Should have	Due date:
Assignee: Sybille Peters	% Done: 100%
Category: Linkvalidator	Estimated time: 0.00 hour
Target version:	Complexity:
TYPO3 Version: 9	Sprint Focus:
PHP Version:	
Tags:	
Description see decisions:Breaking LinkValidator Can be converted to JSON as suggested in #83338 for scheduler. Specifically the field tx_linkvalidator_link.url_response is used to handle results of link check, including the error message: It may contain something like this: <pre>a:2:{s:5:"valid";b:0;s:11:"errorParams";a:2:{s:9:"errorType";s:7:"network";s:7:"message";s:30:"Network error / invalid domain";}}</pre> So, we have: <ul style="list-style-type: none">• bool valid (currently only used if <code>_GP('showalllinks')</code> is set, not really used, maybe we can remove this entirely) errorParams array: <ul style="list-style-type: none">• string errorType• string message (should be removed also, we should get the error message when generating the report, depending on current language of BE user)• exception some depends on type of link: page (internal) link: <ul style="list-style-type: none">• in addition to errorType and message: contains additional information about page / content element Also, the errorParams array includes an errorType and the (localized) error message. This does not really make sense anyway, because it is localized while checking links. It should be localized while viewing results because checking links and viewing the results may be done by different users at different times (and checking may also be done via the scheduler). I am not creating another issue for this, but this should be considered when handling the array differently. It might also make sense to store the errorType in a separate database field for easier aggregation of results.	
Subtasks: Task # 89944: Remove serialization within linkvalidator storage Closed	
Related issues: Related to TYPO3 Core - Feature #83338: Move scheduler tasks from serialized ... Closed 2017-12-15 Related to TYPO3 Core - Task #88991: Unify handling of errorParams in linkval... New 2019-08-21	

History

#1 - 2018-04-30 12:38 - Susanne Moog

- Related to Feature #83338: Move scheduler tasks from serialized data to JSON added

#2 - 2018-04-30 13:44 - Sybille Peters

- Subject changed from *Reconsider serialized array* to *Reconsider serialized array for Linkvalidator*

#3 - 2018-04-30 13:45 - Sybille Peters

- Description updated

#4 - 2018-05-14 22:55 - Sybille Peters

- Parent task set to #85006

#5 - 2019-09-16 07:34 - Sybille Peters

- Description updated

#6 - 2019-09-16 07:36 - Sybille Peters

- Related to Task #88991: *Unify handling of errorParams in linkvalidator* added

#7 - 2019-09-18 09:10 - Sybille Peters

- Description updated

#8 - 2019-11-10 09:09 - Sybille Peters

- Parent task deleted (#85006)

#9 - 2019-12-14 08:53 - Sybille Peters

- Description updated

#10 - 2020-01-09 20:30 - Georg Ringer

- Status changed from *New* to *Closed*

closed as solved with [#89944](#)