

## TYPO3 Core - Bug #85310

### \$GLOBALS['BE\_USER] is null causes Errors in FE

2018-06-19 15:23 - Julian Stelzer

<b>Status:</b> Closed	<b>Start date:</b> 2018-06-19
<b>Priority:</b> Should have	<b>Due date:</b>
<b>Assignee:</b>	<b>% Done:</b> 100%
<b>Category:</b>	<b>Estimated time:</b> 0.00 hour
<b>Target version:</b> 9.4	<b>Complexity:</b>
<b>TYPO3 Version:</b> 9	<b>Is Regression:</b>
<b>PHP Version:</b> 7.2	<b>Sprint Focus:</b>
<b>Tags:</b>	
<b>Description</b>	
Call to a member function <code>getTSConfig()</code> on null Error thrown in file <code>../typo3/sysext/backend/Classes/Utility/BackendUtility.php</code> in line 873.	
Trying to save data of a form in my database in Frontend.	
The error comes from this line:	
<pre>\$userTSconfig = static::getBackendUserAuthentication()-&gt;getTSConfig() ?? [];</pre>	
static::getBackendUserAuthentication() is null.	
<b>Related issues:</b>	
Related to TYPO3 Core - Task #82497: Streamline \TYPO3\CMS\Backend\Utility\Ba...	<b>Closed</b> <b>2017-09-17</b>

#### Associated revisions

##### Revision 3260e93 - 2018-09-04 10:03 - Benni Mack

[BUGFIX] Allow `getPagesTSconfig` to be called without `BE_USER`

Due to refactorings lately in `BackendUtility::getPagesTSconfig()` with which results in a fatal error when clearing page cache while persisting an extbase object.

The patch adds a test without a Backend User, and encapsulates this with a simple `if()` statement. However, this also shows that some other areas that are touched are not fully notice-free / strict, which are tackled as well.

Resolves: #85310

Releases: master

Change-Id: I0f1318d395451e704e1783e841d96583efe2a560

Reviewed-on: <https://review.typo3.org/58174>

Reviewed-by: Andreas Fernandez <[a.fernandez@scripting-base.de](mailto:a.fernandez@scripting-base.de)>

Tested-by: TYPO3com <[no-reply@typo3.com](mailto:no-reply@typo3.com)>

Reviewed-by: Oliver Hader <[oliver.hader@typo3.org](mailto:oliver.hader@typo3.org)>

Reviewed-by: Susanne Moog <[susanne.moog@typo3.org](mailto:susanne.moog@typo3.org)>

Reviewed-by: Daniel Goerz <[daniel.goerz@posteo.de](mailto:daniel.goerz@posteo.de)>

Tested-by: Susanne Moog <[susanne.moog@typo3.org](mailto:susanne.moog@typo3.org)>

Reviewed-by: Markus Klein <[markus.klein@typo3.org](mailto:markus.klein@typo3.org)>

Tested-by: Markus Klein <[markus.klein@typo3.org](mailto:markus.klein@typo3.org)>

#### History

##### #1 - 2018-06-19 15:26 - Julian Stelzer

- Project changed from 9 to TYPO3 Core

- Target version set to 9.4

- TYPO3 Version set to 9

- PHP Version set to 7.2

## #2 - 2018-06-21 06:33 - Georg Ringer

- Status changed from New to Needs Feedback

BackendUtility is for the backend as the name suggests. what are you doing exactly to get this error? you can also initialize the \$GLOBALS['BE\_USER'] yourself in the FE.

## #3 - 2018-06-21 09:05 - Julian Stelzer

Georg Ringer wrote:

BackendUtility is for the backend as the name suggests. what are you doing exactly to get this error? you can also initialize the \$GLOBALS['BE\_USER'] yourself in the FE.

I try to save some modeldata in my FE with the add-function of \TYPO3\CMS\Extbase\Persistence\Repository. I dont want to use the \$GLOBALS['BE\_USER'] or the BackendUtility-Class on my own, but TYPO3 is doing that for me and it causes this error. The same function works great in TYPO3 7.6.

## #4 - 2018-06-25 16:35 - Jan Schröder

In TYPO3 8.x the function getTSConfig work without and Backend Login.  
Since TYPO3 9 the getTSConfig is not working anymore in Frontend Context.

Is there a way to create the missing \$GLOBALS['BE\_USER'] or is there another way to get the TSConfig in frontend context?

The breaking change is not documented and broke the gridelements extension :-)

## #5 - 2018-07-04 08:34 - Julian Stelzer

It currently breaks all extensions, which write from Frontend into Database and use the repository methods.

Quickfix:

```
$userTSconfig = [];  
if( static::getBackendUserAuthentication() ){  
    $userTSconfig = static::getBackendUserAuthentication()->getTSConfig() ?? [];  
}  
  
//$userTSconfig = static::getBackendUserAuthentication()->getTSConfig() ?? [];
```

But it should be fixed soon.

## #6 - 2018-07-27 09:58 - Sinisa Mitrovic

Another quick fix can be initializing BE User before fetching getPagesTSconfig.

```
if($GLOBALS['BE_USER'] === null) {  
    $GLOBALS['BE_USER'] = GeneralUtility::makeInstance(  
'TYPO3\CMS\Core\Authentication\BackendUserAuthentication');  
    $GLOBALS['BE_USER']->start();  
}
```

## #7 - 2018-08-09 08:41 - sonal vadhavana

yes, this solution works fine but needs to improve by this one:

First include the namespace and then write code: Otherwise give deprecation error.

use TYPO3\CMS\Core\Authentication\BackendUserAuthentication;

```
if($GLOBALS['BE_USER'] === null) {  
    $GLOBALS['BE_USER'] = GeneralUtility::makeInstance(BackendUserAuthentication::class);  
    $GLOBALS['BE_USER']->start();  
}
```

## #8 - 2018-08-13 13:43 - Thomas Kieslich

If this doesn't work try to set enabledBeUserIPlock to false. checkLockToIP() is called before your own Controller.

## #9 - 2018-09-03 15:17 - Susanne Moog

- Status changed from Needs Feedback to Accepted

Problem seems to be that `\\TYPO3\CMS\Extbase\Persistence\Generic\Storage\Typo3DbBackend::clearPageCache` calls `$pageTS = BackendUtility::getPagesTSconfig($storagePage)` in case of write operations with extbase (delete, update, add), which in turn needs a valid backend user.`

**#10 - 2018-09-04 09:06 - Benni Mack**

- *Related to Task #82497: Streamline `\\TYPO3\CMS\Backend\Utility\BackendUtility::getPagesTSconfig` added*

**#11 - 2018-09-04 09:08 - Gerrit Code Review**

- *Status changed from Accepted to Under Review*

Patch set 1 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server.

It is available at <https://review.typo3.org/58174>

**#12 - 2018-09-04 10:30 - Benni Mack**

- *Status changed from Under Review to Resolved*

- *% Done changed from 0 to 100*

Applied in changeset [3260e09382068949e03cf4d6ca2a497275c2671e](https://review.typo3.org/58174).

**#13 - 2018-10-02 10:44 - Benni Mack**

- *Status changed from Resolved to Closed*