

TYPO3 Core - Bug #91423

Database Upgrade Wizard row size is to large but processes with upgrade wizards without error reporting

2020-05-18 06:54 - Benjamin Franzke

Status:	Under Review	Start date:	2020-05-18
Priority:	Should have	Due date:	
Assignee:		% Done:	0%
Category:	Install Tool	Estimated time:	0.00 hour
Target version:	Candidate for patchlevel	Complexity:	
TYPO3 Version:	10	Is Regression:	
PHP Version:	7.2	Sprint Focus:	
Tags:			

Description

Updating from TYPO3 v8 (directly) to v10 on Mariadb 10.3.22 the database upgrade field-additions operation causes errors because the row size is too large for some tables (pages, be_users, be_groups and tt_content in my case).

This is the table structure that is currently causes error on my system:

```
CREATE TABLE `pages` (  
  `uid` int(11) NOT NULL AUTO_INCREMENT,  
  `pid` int(11) NOT NULL DEFAULT 0,  
  `t3ver_oid` int(11) NOT NULL DEFAULT 0,  
  `t3ver_id` int(11) NOT NULL DEFAULT 0,  
  `t3ver_wsid` int(11) NOT NULL DEFAULT 0,  
  `t3ver_label` varchar(255) NOT NULL DEFAULT '',  
  `t3ver_state` smallint(6) NOT NULL DEFAULT 0,  
  `t3ver_stage` int(11) NOT NULL DEFAULT 0,  
  `t3ver_count` int(11) NOT NULL DEFAULT 0,  
  `t3ver_tstamp` int(11) NOT NULL DEFAULT 0,  
  `t3ver_move_id` int(11) NOT NULL DEFAULT 0,  
  `t3_origuid` int(11) NOT NULL DEFAULT 0,  
  `tstamp` int(11) unsigned NOT NULL DEFAULT 0,  
  `sorting` int(11) unsigned NOT NULL DEFAULT 0,  
  `deleted` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `perms_userid` int(11) unsigned NOT NULL DEFAULT 0,  
  `perms_groupid` int(11) unsigned NOT NULL DEFAULT 0,  
  `perms_user` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `perms_group` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `perms_everybody` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `editlock` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `crdate` int(11) unsigned NOT NULL DEFAULT 0,  
  `cruser_id` int(11) unsigned NOT NULL DEFAULT 0,  
  `hidden` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `title` varchar(255) NOT NULL DEFAULT '',  
  `doktype` int(11) unsigned NOT NULL DEFAULT 0,  
  `TSconfig` text DEFAULT NULL,  
  `is_siteroot` smallint(6) NOT NULL DEFAULT 0,  
  `php_tree_stop` smallint(6) NOT NULL DEFAULT 0,  
  `tx_impexp_origuid` int(11) NOT NULL DEFAULT 0,  
  `url` varchar(255) NOT NULL DEFAULT '',  
  `starttime` int(11) unsigned NOT NULL DEFAULT 0,  
  `endtime` int(11) unsigned NOT NULL DEFAULT 0,  
  `urltype` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `shortcut` int(10) unsigned NOT NULL DEFAULT 0,  
  `shortcut_mode` int(10) unsigned NOT NULL DEFAULT 0,  
  `no_cache` int(10) unsigned NOT NULL DEFAULT 0,  
  `fe_group` varchar(100) NOT NULL DEFAULT '0',  
  `subtitle` varchar(255) NOT NULL DEFAULT '',  
  `layout` int(11) unsigned NOT NULL DEFAULT 0,
```

```

`target` varchar(80) NOT NULL DEFAULT '',
`media` int(11) unsigned NOT NULL DEFAULT 0,
`lastUpdated` int(10) unsigned NOT NULL DEFAULT 0,
`keywords` text DEFAULT NULL,
`cache_timeout` int(10) unsigned NOT NULL DEFAULT 0,
`cache_tags` varchar(255) NOT NULL DEFAULT '',
`newUntil` int(10) unsigned NOT NULL DEFAULT 0,
`description` text DEFAULT NULL,
`no_search` smallint(5) unsigned NOT NULL DEFAULT 0,
`SYS_LASTCHANGED` int(10) unsigned NOT NULL DEFAULT 0,
`abstract` text DEFAULT NULL,
`module` varchar(255) NOT NULL DEFAULT '',
`extendToSubpages` smallint(5) unsigned NOT NULL DEFAULT 0,
`author` varchar(255) NOT NULL DEFAULT '',
`author_email` varchar(80) NOT NULL DEFAULT '',
`nav_title` varchar(255) NOT NULL DEFAULT '',
`nav_hide` smallint(6) NOT NULL DEFAULT 0,
`content_from_pid` int(10) unsigned NOT NULL DEFAULT 0,
`mount_pid` int(10) unsigned NOT NULL DEFAULT 0,
`mount_pid_ol` smallint(6) NOT NULL DEFAULT 0,
`alias` varchar(32) NOT NULL DEFAULT '',
`l18n_cfg` smallint(6) NOT NULL DEFAULT 0,
`fe_login_mode` smallint(6) NOT NULL DEFAULT 0,
`backend_layout` varchar(64) NOT NULL DEFAULT '',
`backend_layout_next_level` varchar(64) NOT NULL DEFAULT '',
`tsconfig_includes` text DEFAULT NULL,
`categories` int(11) NOT NULL DEFAULT 0,
`tx_realurl_pathsegment` varchar(255) NOT NULL DEFAULT '',
`tx_realurl_pathoverride` int(1) NOT NULL DEFAULT 0,
`tx_realurl_exclude` int(1) NOT NULL DEFAULT 0,
`tx_realurl_nocache` int(1) NOT NULL DEFAULT 0,
PRIMARY KEY (`uid`),
KEY `t3ver_oid` (`t3ver_oid`,`t3ver_wsid`),
KEY `parent` (`pid`,`deleted`,`sorting`),
KEY `alias` (`alias`),
KEY `determineSiteRoot` (`is_siteroot`)
) ENGINE=InnoDB AUTO_INCREMENT=13 DEFAULT CHARSET=utf8

```

```

CREATE TABLE `be_groups` (
`uid` int(11) unsigned NOT NULL AUTO_INCREMENT,
`pid` int(11) unsigned NOT NULL DEFAULT 0,
`tstamp` int(11) unsigned NOT NULL DEFAULT 0,
`title` varchar(50) NOT NULL DEFAULT '',
`non_exclude_fields` text DEFAULT NULL,
`explicit_allowdeny` text DEFAULT NULL,
`allowed_languages` varchar(255) NOT NULL DEFAULT '',
`custom_options` text DEFAULT NULL,
`db_mountpoints` text DEFAULT NULL,
`pagetypes_select` varchar(255) NOT NULL DEFAULT '',
`tables_select` text DEFAULT NULL,
`tables_modify` text DEFAULT NULL,
`crdate` int(11) unsigned NOT NULL DEFAULT 0,
`cruser_id` int(11) unsigned NOT NULL DEFAULT 0,
`groupMods` text DEFAULT NULL,
`file_mountpoints` text DEFAULT NULL,
`file_permissions` text DEFAULT NULL,
`hidden` smallint(5) unsigned NOT NULL DEFAULT 0,
`description` varchar(2000) NOT NULL DEFAULT '',
`lockToDomain` varchar(50) NOT NULL DEFAULT '',
`deleted` smallint(5) unsigned NOT NULL DEFAULT 0,
`TSconfig` text DEFAULT NULL,
`subgroup` text DEFAULT NULL,
`hide_in_lists` smallint(6) NOT NULL DEFAULT 0,
`workspace_perms` smallint(6) NOT NULL DEFAULT 1,
`category_perms` text DEFAULT NULL,
PRIMARY KEY (`uid`),
KEY `parent` (`pid`)

```

```
) ENGINE=InnoDB AUTO_INCREMENT=2 DEFAULT CHARSET=utf8
```

```
CREATE TABLE `be_users` (  
  `uid` int(11) unsigned NOT NULL AUTO_INCREMENT,  
  `pid` int(11) unsigned NOT NULL DEFAULT 0,  
  `tstamp` int(11) unsigned NOT NULL DEFAULT 0,  
  `username` varchar(50) NOT NULL DEFAULT '',  
  `description` varchar(2000) NOT NULL DEFAULT '',  
  `avatar` int(11) unsigned NOT NULL DEFAULT 0,  
  `password` varchar(100) NOT NULL DEFAULT '',  
  `admin` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `usergroup` varchar(255) NOT NULL DEFAULT '',  
  `disable` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `starttime` int(11) unsigned NOT NULL DEFAULT 0,  
  `endtime` int(11) unsigned NOT NULL DEFAULT 0,  
  `lang` varchar(6) NOT NULL DEFAULT '',  
  `email` varchar(80) NOT NULL DEFAULT '',  
  `db_mountpoints` text DEFAULT NULL,  
  `options` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `crdate` int(11) unsigned NOT NULL DEFAULT 0,  
  `cruser_id` int(11) unsigned NOT NULL DEFAULT 0,  
  `realName` varchar(80) NOT NULL DEFAULT '',  
  `userMods` text DEFAULT NULL,  
  `allowed_languages` varchar(255) NOT NULL DEFAULT '',  
  `uc` mediumblob DEFAULT NULL,  
  `file_mountpoints` text DEFAULT NULL,  
  `file_permissions` text DEFAULT NULL,  
  `workspace_perms` smallint(6) NOT NULL DEFAULT 1,  
  `lockToDomain` varchar(50) NOT NULL DEFAULT '',  
  `disableIPlock` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `deleted` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `TSconfig` text DEFAULT NULL,  
  `lastlogin` int(10) unsigned NOT NULL DEFAULT 0,  
  `createdByAction` int(11) NOT NULL DEFAULT 0,  
  `usergroup_cached_list` text DEFAULT NULL,  
  `workspace_id` int(11) NOT NULL DEFAULT 0,  
  `workspace_preview` smallint(6) NOT NULL DEFAULT 1,  
  `category_perms` text DEFAULT NULL,  
  PRIMARY KEY (`uid`),  
  KEY `parent` (`pid`),  
  KEY `username` (`username`)  
) ENGINE=InnoDB AUTO_INCREMENT=7 DEFAULT CHARSET=utf8
```

```
CREATE TABLE `tt_content` (  
  `uid` int(11) NOT NULL AUTO_INCREMENT,  
  `pid` int(11) NOT NULL DEFAULT 0,  
  `t3ver_oid` int(11) NOT NULL DEFAULT 0,  
  `t3ver_id` int(11) NOT NULL DEFAULT 0,  
  `t3ver_wsid` int(11) NOT NULL DEFAULT 0,  
  `t3ver_label` varchar(255) NOT NULL DEFAULT '',  
  `t3ver_state` smallint(6) NOT NULL DEFAULT 0,  
  `t3ver_stage` int(11) NOT NULL DEFAULT 0,  
  `t3ver_count` int(11) NOT NULL DEFAULT 0,  
  `t3ver_tstamp` int(11) NOT NULL DEFAULT 0,  
  `t3ver_move_id` int(11) NOT NULL DEFAULT 0,  
  `t3_origuid` int(11) NOT NULL DEFAULT 0,  
  `tstamp` int(11) unsigned NOT NULL DEFAULT 0,  
  `crdate` int(11) unsigned NOT NULL DEFAULT 0,  
  `cruser_id` int(11) unsigned NOT NULL DEFAULT 0,  
  `editlock` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `hidden` smallint(5) unsigned NOT NULL DEFAULT 0,  
  `sorting` int(11) unsigned NOT NULL DEFAULT 0,  
  `CType` varchar(255) NOT NULL DEFAULT '',  
  `header` varchar(255) NOT NULL DEFAULT '',  
  `rowDescription` text DEFAULT NULL,  
  `bodytext` mediumtext DEFAULT NULL,  
  `image` int(11) unsigned NOT NULL DEFAULT 0,
```

```

`imagewidth` mediumint(11) unsigned NOT NULL DEFAULT 0,
`imageorient` smallint(5) unsigned NOT NULL DEFAULT 0,
`imagecols` smallint(5) unsigned NOT NULL DEFAULT 0,
`imageborder` smallint(5) unsigned NOT NULL DEFAULT 0,
`media` int(11) unsigned NOT NULL DEFAULT 0,
`layout` varchar(255) NOT NULL DEFAULT '',
`deleted` smallint(5) unsigned NOT NULL DEFAULT 0,
`cols` int(11) unsigned NOT NULL DEFAULT 0,
`records` text DEFAULT NULL,
`pages` text DEFAULT NULL,
`starttime` int(11) unsigned NOT NULL DEFAULT 0,
`endtime` int(11) unsigned NOT NULL DEFAULT 0,
`colPos` smallint(6) NOT NULL DEFAULT 0,
`subheader` varchar(255) NOT NULL DEFAULT '',
`fe_group` varchar(100) NOT NULL DEFAULT '0',
`header_link` varchar(1024) NOT NULL DEFAULT '',
`image_zoom` smallint(5) unsigned NOT NULL DEFAULT 0,
`header_layout` varchar(30) NOT NULL DEFAULT '0',
`list_type` varchar(255) NOT NULL DEFAULT '',
`sectionIndex` smallint(5) unsigned NOT NULL DEFAULT 0,
`linkToTop` smallint(5) unsigned NOT NULL DEFAULT 0,
`file_collections` text DEFAULT NULL,
`filelink_size` smallint(5) unsigned NOT NULL DEFAULT 0,
`filelink_sorting` varchar(10) NOT NULL DEFAULT '',
`target` varchar(30) NOT NULL DEFAULT '',
`date` int(10) unsigned NOT NULL DEFAULT 0,
`recursive` smallint(5) unsigned NOT NULL DEFAULT 0,
`imageheight` mediumint(8) unsigned NOT NULL DEFAULT 0,
`sys_language_uid` int(11) NOT NULL DEFAULT 0,
`tx_impexp_origuid` int(11) NOT NULL DEFAULT 0,
`pi_flexform` mediumtext DEFAULT NULL,
`accessibility_title` varchar(30) NOT NULL DEFAULT '',
`accessibility_bypass` smallint(5) unsigned NOT NULL DEFAULT 0,
`accessibility_bypass_text` varchar(30) NOT NULL DEFAULT '',
`l18n_parent` int(11) NOT NULL DEFAULT 0,
`l18n_diffsource` mediumblob DEFAULT NULL,
`selected_categories` text DEFAULT NULL,
`category_field` varchar(64) NOT NULL DEFAULT '',
`table_caption` varchar(255) DEFAULT NULL,
`table_delimiter` smallint(6) unsigned NOT NULL DEFAULT 0,
`table_enclosure` smallint(6) unsigned NOT NULL DEFAULT 0,
`table_header_position` smallint(5) unsigned NOT NULL DEFAULT 0,
`table_tfoot` smallint(5) unsigned NOT NULL DEFAULT 0,
`bullets_type` smallint(5) unsigned NOT NULL DEFAULT 0,
`uploads_description` smallint(5) unsigned NOT NULL DEFAULT 0,
`uploads_type` smallint(5) unsigned NOT NULL DEFAULT 0,
`assets` int(11) unsigned NOT NULL DEFAULT 0,
`categories` int(11) NOT NULL DEFAULT 0,
`backupColPos` smallint(6) NOT NULL DEFAULT -2,
`tx_gridelements_backend_layout` varchar(255) NOT NULL DEFAULT '',
`tx_gridelements_children` int(11) NOT NULL DEFAULT 0,
`tx_gridelements_container` int(11) NOT NULL DEFAULT 0,
`tx_gridelements_columns` int(11) NOT NULL DEFAULT 0,
`header_position` varchar(6) NOT NULL DEFAULT '',
`spaceAfter` smallint(5) unsigned NOT NULL DEFAULT 0,
`spaceBefore` smallint(5) unsigned NOT NULL DEFAULT 0,
`frame_class` varchar(60) NOT NULL DEFAULT 'default',
`space_before_class` varchar(60) NOT NULL DEFAULT '',
`space_after_class` varchar(60) NOT NULL DEFAULT '',
`table_class` varchar(60) NOT NULL DEFAULT '',
`l10n_source` int(11) NOT NULL DEFAULT 0,
`l10n_state` text DEFAULT NULL,
PRIMARY KEY (`uid`),
KEY `t3ver_oid` (`t3ver_oid`,`t3ver_wsid`),
KEY `parent` (`pid`,`sorting`),
KEY `language` (`l18n_parent`,`sys_language_uid`),
KEY `gridelements` (`tx_gridelements_container`,`tx_gridelements_columns`)

```

```
) ENGINE=InnoDB AUTO_INCREMENT=14 DEFAULT CHARSET=utf8
```

Current Behaviour

Now, errors were not reported when running "Create missing tables and fields". The `upgradeWizardsBlockingDatabaseExecute` ajax action always reports success and doesn't check for errors, therefore the install tool javascript continues to request all available wizards.

These wizards then fail because the database requirements were not added successfully (in my case the `pages.slug` field was missing which causes `PagesSlugMigrator::updateNecessary` to fail).

Therefore the following exception occurred:


```
An exception occurred while executing 'SELECT COUNT(`uid`) FROM `pages` WHERE ((`slug` = ?) OR (`slug` IS NULL)) AND (`pages`.`deleted` = 0)' with params [ ]: Unknown column 'slug' in 'where clause'
```

Something went wrong. Please use **Check for broken extensions** to see if a loaded extension breaks this part of the install tool and unload it.

The box below may additionally reveal further details on what went wrong depending on your debug settings. It may help to temporarily switch to debug mode using **Settings > Configuration Presets > Debug settings**.

If this error happens at an early state and no full exception back trace is shown, it may also help to manually increase debugging output in `typo3conf/LocalConfiguration.php` ; `['BE']['debug'] => true` ; `['SYS']['devIPmask'] => '*'` ; `['SYS']['displayErrors'] => 1` ; `['SYS']['systemLogLevel'] => 0` ; `['SYS']['exceptionalErrors'] => 12290`

→ Ajax error

 Whoops, looks like something went wrong.

(1/2) Doctrine\DBAL\Exception\InvalidFieldNameException

An exception occurred while executing 'SELECT COUNT(uid) FROM 'pages' WHERE ((slug = ?) OR (slug IS NULL)) AND ('pages'.deleted = 0)' with params [{}]: Unknown column 'slug' in 'where clause'

in /home/ben/efgb/efg-project/vendor/doctrine/dbal/lib/Doctrine/DBAL/Driver/AbstractMySQLDriver.php line 60

```
56         case '1054':
57         case '1166':
58         case '1611':
59             return new Exception\InvalidFieldNameException($message, $exception);
60
61
62         case '1052':
63         case '1060':
64         case '1110':
```

at Doctrine\DBAL\Driver\AbstractMySQLDriver->convertException(An exception occurred while executing 'SELECT COUNT(uid) FROM 'pages' WHERE ((slug = ?) OR (slug IS NULL)) AND ('pages'.deleted = 0)' with params [{}]: Unknown column 'slug' in 'where clause', object(Doctrine\DBAL\Driver\Mysqli\MysqliException))

in /home/ben/efgb/efg-project/vendor/doctrine/dbal/lib/Doctrine/DBAL/DBALException.php line 169

```
165         if ($driverEx instanceof DriverException) {
166             return $driverEx;
167         }
168         if ($driver instanceof ExceptionConverterDriver && $driverEx instanceof DriverExceptionInterface) {
169             return $driver->convertException($msg, $driverEx);
170         }
171         return new self($msg, 0, $driverEx);
172     }
173 }
```

at Doctrine\DBAL\DBALException::wrapException(object(Doctrine\DBAL\Driver\Mysqli\Driver), object(Doctrine\DBAL\Driver\Mysqli\MysqliException), 'An exception occurred while executing 'SELECT COUNT(uid) FROM 'pages' WHERE ((slug = ?) OR (slug IS NULL)) AND ('pages'.deleted = 0)' with params [{}]: Unknown column 'slug' in 'where clause')'

in /home/ben/efgb/efg-project/vendor/doctrine/dbal/lib/Doctrine/DBAL/DBALException.php line 149

```
145         $msg .= ' with params ' . self::formatParameters($params);
146     }
147     $msg .= "\n\n" . $driverEx->getMessage();
148
149     return static::wrapException($driver, $driverEx, $msg);
150 }
151
152 /**
153  * @return self
```

at Doctrine\DBAL\DBALException::driverExceptionDuringQuery(object(Doctrine\DBAL\Driver\Mysqli\Driver), object(Doctrine\DBAL\Driver\Mysqli\MysqliException), 'SELECT COUNT(uid) FROM 'pages' WHERE ((slug = ?) OR (slug IS NULL)) AND ('pages'.deleted = 0)', array())

in /home/ben/efgb/efg-project/vendor/doctrine/dbal/lib/Doctrine/DBAL/Connection.php line 914

```
910         } else {
911             $stmt = $connection->query($query);
912         }
913     } catch (Throwable $ex) {
914         throw DBALException::driverExceptionDuringQuery($this->driver, $ex, $query, $this->resolveParams($params, $types));
915     }
916     $stmt->setFetchMode($this->defaultFetchMode);
917
918 }
```

at Doctrine\DBAL\Connection->executeQuery('SELECT COUNT(uid) FROM 'pages' WHERE ((slug = ?) OR (slug IS NULL)) AND ('pages'.deleted = 0)', array(), array(2))

in /home/ben/efgb/efg-project/vendor/doctrine/dbal/lib/Doctrine/DBAL/Query/QueryBuilder.php line 206

```
202     */
203     public function execute()
204     {
205         if ($this->type === self::SELECT) {
206             return $this->connection->executeQuery($this->getSQL(), $this->params, $this->paramTypes);
207         }
208
209         return $this->connection->executeUpdate($this->getSQL(), $this->params, $this->paramTypes);
210     }
211 }
```

at Doctrine\DBAL\Query\QueryBuilder->execute()

in /home/ben/efgb/efg-project/web/typo3/sysext/core/Classes/Database/Query/QueryBuilder.php line 204

```
200
201     // Set additional query restrictions
202     $originalWhereConditions = $this->addAdditionalWhereConditions();
203
204     $result = $this->concreteQueryBuilder->execute();
205
206     // Restore the original query conditions in case the user keeps
207     // on modifying the state.
208     $this->concreteQueryBuilder->add('where', $originalWhereConditions, false);
```

at TYPO3\CMS\Core\Database\Query\QueryBuilder->execute()

in /home/ben/efgb/efg-project/web/typo3/sysext/install/Classes/Updates/PopulatePageSlugs.php line 217

```
213         $queryBuilder->expr()->eq($this->fieldName, $queryBuilder->createNamedParameter(''));
214         $queryBuilder->expr()->isNull($this->fieldName)
215     )
216     )
217     ->execute()
218     ->fetchColumn();
219     return $numberOfEntries > 0;
220 }
221 }
```

at TYPO3\CMS\Install\Updates\PopulatePageSlugs->checkIfWizardIsRequired()

in /home/ben/efgb/efg-project/web/typo3/sysext/install/Classes/Updates/PopulatePageSlugs.php line 84

Expected Result

I would have expected the install tool to present the following list of errors that occurred during tables and fields addition (note this list of errors has been retrieved using a patch to upgradeWizardsBlockingDatabaseExecute):

```
Failed to execute: ALTER TABLE be_groups ADD `availableWidgets` TEXT DEFAULT NULL
Row size too large. The maximum row size for the used table type, not counting BLOBs, is 8126. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBs

Failed to execute: ALTER TABLE be_users ADD `password_reset_token` VARCHAR(100) DEFAULT '' NOT NULL
Row size too large. The maximum row size for the used table type, not counting BLOBs, is 8126. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBs

Failed to execute: ALTER TABLE pages ADD `rowDescription` TEXT DEFAULT NULL, ADD `sys_language_uid` INT DEFAULT 0 NOT NULL, ADD `l10n_source` INT UNSIGNED DEFAULT 0 NOT NULL, ADD `l10n_state` TEXT DEFAULT NULL, ADD `l10n_diffsource` MEDIUMBLOB DEFAULT NULL, ADD `slug` VARCHAR(2048) DEFAULT NULL, ADD `legacy_overlay_uid` INT UNSIGNED DEFAULT 0 NOT NULL, ADD `l10n_parent` INT UNSIGNED DEFAULT 0 NOT NULL
Row size too large. The maximum row size for the used table type, not counting BLOBs, is 8126. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBs

Failed to execute: CREATE INDEX `language_identifier` ON pages (l10n_parent, sys_language_uid)
Key column 'l10n_parent' doesn't exist in table

Failed to execute: CREATE INDEX `slug` ON pages (slug(127))
Key column 'slug' doesn't exist in table

Failed to execute: CREATE INDEX `translation_source` ON pages (l10n_source)
Key column 'l10n_source' doesn't exist in table

Failed to execute: ALTER TABLE tt_content ADD `filelink_sorting_direction` VARCHAR(4) DEFAULT '' NOT NULL, ADD `gridelements_shortcut_page_order_by` INT DEFAULT 0 NOT NULL
Row size too large. The maximum row size for the used table type, not counting BLOBs, is 8126. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBs
```

History

#1 - 2020-05-18 07:10 - Gerrit Code Review

- Status changed from New to Under Review

Patch set 1 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server. It is available at <https://review.typo3.org/c/Packages/TYPO3.CMS/+64509>

#2 - 2020-05-25 20:53 - Gerrit Code Review

Patch set 2 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server. It is available at <https://review.typo3.org/c/Packages/TYPO3.CMS/+64509>

#3 - 2020-06-04 10:55 - Gerrit Code Review

Patch set 3 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server. It is available at <https://review.typo3.org/c/Packages/TYPO3.CMS/+64509>

Files

upgrade-wizard-list-slug-error.png	397 KB	2020-05-18	Benjamin Franzke
------------------------------------	--------	------------	------------------