

TYPO3 Core - Feature #93644

includeCSS should have options for rel="preload"

2021-03-04 09:13 - David Bruchmann

Status:	Needs Feedback	Start date:	2021-03-04
Priority:	Should have	Due date:	
Assignee:		% Done:	0%
Category:	Fluid	Estimated time:	0.00 hour
Target version:		Complexity:	
PHP Version:		Sprint Focus:	
Tags:			
Description			
Having this desired HTML:			
<pre><link rel="preload" href="/typo3conf/ext/sitepackage/Resources/Public/Fonts/Adelle-Bold.woff" as="font" title="FontHeadingsBold" type="font/woff" crossorigin="anonymous" /> <link rel="preload" href="/typo3conf/ext/sitepackage/Resources/Public/Fonts/Adelle-Bold.woff" as="font" title="FontHeadingsRegular" type="font/woff" crossorigin="anonymous" /> <link rel="preload" href="/typo3conf/ext/sitepackage/Resources/Public/Fonts/GothamNarrSSm-Book_Web.woff" as="font" title="FontRegular" type="font/woff" crossorigin="anonymous" /> <link rel="preload" href="/typo3conf/ext/sitepackage/Resources/Public/Fonts/GothamSSm-Medium_Web.woff" as="font" title="FontBold" type="font/woff" crossorigin="anonymous" /> <link rel="stylesheet" href="/typo3conf/ext/sitepackage/Resources/Public/Css/fonts.css" crossorigin="anonymous" /></pre>			
and this content in fonts.css:			
<pre>@font-face {font-family: "FontRegular"; src: url("/typo3conf/ext/sitepackage/Resources/Public/Fonts/GothamNarrSSm-Book_Web.woff") format("woff"); font-display: swap;} @font-face {font-family: "FontBold"; src: url("/typo3conf/ext/sitepackage/Resources/Public/Fonts/GothamSSm-Medium_Web.woff") format("woff"); font-display: swap;} @font-face {font-family: "FontHeadingsRegular"; src: url("/typo3conf/ext/sitepackage/Resources/Public/Fonts/Adelle-Bold.woff") format("woff"); font-display: swap;} @font-face {font-family: "FontHeadingsBold"; src: url("/typo3conf/ext/sitepackage/Resources/Public/Fonts/Adelle-Bold.woff") format("woff"); font-display: swap;}</pre>			
I don't see an option how to achieve it differently by TypoScript than as comment.			
The feature request is to increase the amount of options, so that the desired code can be created in top of the css-files.			

History

#1 - 2021-03-04 14:00 - Christian Hackl

Just as a hint if you were not yet aware of this:

You can already implement this with FLUID:

<https://docs.typo3.org/other/typo3/view-helper-reference/10.4/en-us/typo3/fluid/latest/Asset/Css.html>

(In my opinion, it is better to load css and js via FLUID / ViewHelper instead of TypoScript).

Example for fluid.assets :

https://github.com/Hauer-Heinrich/hh_theme_default/tree/master/Resources/Private/Theme/Partials/Assets

#2 - 2021-03-04 15:28 - David Bruchmann

Thanks, that's a good hint.

I never used fluid yet for the head-area and missed the assets-options.

#3 - 2021-03-30 20:23 - Riccardo De Contardi

- Category set to Fluid

- Status changed from New to Needs Feedback

@David Bruchmann is the answer sufficient for you? Is there still something missing?